





• UFR.3.NC180.NM

• UFDR.3.NC180.NM

TECHNICAL DATA

Mode of Operation	:	Non-Maintained
Lamp	:	3W High Power LED
Rated Duration	:	3 hrs and others
Mains Supply	:	230 Volts, 50/60Hz
Power Consumption	:	< 1.4W
Battery	:	High temp Nickel Cadmium
Charge Monitor	:	Green LED
Test Facility	:	Tactile switch
Safety Feature	:	Low volt cut-off preventing battery overdischarge
Fitting Construction	:	Electro galvanised steel with epoxy powder coating
Mounting	:	Recess
Weight	:	0.8kg (gross)
Compliance	:	SS 563 : Part 1 & 2, SS IEC 60598-2-22
Warranty	:	1 year

Dimension: mm NTS High Power L.E.D

KEY FEATURES

- > High Brightness Output
- > High Lumen/watt Efficiency
- > Low Power Consumption
- > Low Maintenance
- > Long Lifespan







Recess Mount Miniature Emergency Luminaire F

IP30 CLASS I



ORDERING GUIDE (Please check with Sales Dept if customisation is required)

л.	UDIDL	1 10030 0	noon wur	Ouros Dopen	00310/1/130110/1/131	oqu

Model	Lamp	Battery type
UFR.3.NC180.NM	3W LED	Nickel Cadmium
UFDR.3.NC180.NM	3W LED	Nickel Cadmium

