

Product page



MALLIA SENSES LEGRAND

Mallia Senses - 1 gang Multistandard switched socket outlet - Matt White

REF. 281120MW | EAN. 3414972072403

The multistandard switched socket allows the supply of power to an electrical device compatible with Euro, US, Indian, Chinese or British standards.

> [Visit e-catalogue](#)

Description

The multistandard switched socket allows the supply of power to an electrical device compatible with Euro, US, Indian, Chinese or British standards.

Product Characteristics

- 2P+E Multi standard, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for a secured & enhanced contacts
- Marked terminals for easy identification
- Matt white finish

Recommendation / Restriction

- Recommended inside use only

The product's benefits

Installation

- Quick and Easy plate clipping system

Usage

- Fitted with safety shutters to maximise child protection

Avantages

- Delivered with its protective shell against paint and dust during installation phase
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

Technical characteristics

Model	Multi-standard socket	Surface protection	Untreated
Protective contact	Other	Surface finishing	Matt
Number of active contacts (round)	2	Antimicrobial treatment	No
Number of active contacts (flat)	2	With on/off switch	Yes
Assembly arrangement	Basic element with full cover plate	Nominal current	16 A
With complementary luminous signal	No	Nominal voltage	250 V
Number of ports USB-A	0	Frequency (Min-Max)	50-60 Hz
		Suitable for degree of protection (IP)	IP20

Number of ports USB-C	0	degree of impact strength (IK)	IK04
Number of socket outlets switchable	1	Device width	86 mm
Imprint/indication	Scanneable symbol/barrier free	Device height	86 mm
Connection type	Screwed terminal	Device depth	33.4 mm
With hinged lid	No	Min. depth of built-in installation box	35 mm
With enhanced contact protection	Yes	Compatible with Apple HomeKit	No
Colour	White	Compatible with Amazon Alexa	No
RAL-number (similar)	9003	Compatible with Google Assistant	No
Metallic colour	No	IFTTT support available	No
Transparent	No	With Wi-Fi signal repeater	No
Lockable	No	With built-in bluetooth speaker	No
Eject-mechanism	No	Built-in depth	23.7 mm
With function lighting	No	Operating / setting temperature (Min-Max)	-5-50 °C
With orientation lighting	No	Storage temperature (Min-Max)	-10-70 °C
Oversupply protection	No	Voltage type	AC
Fault current protection	No	Terminal marking indication	Yes
With miniature fuse	No	Prewired	No
Special power supply	None	Terminals capacity (Min-Max)	1-4 mm ²
Mounting method	Flush-mounted	Cable nature for connection	Flexible or rigid
Type of fastening	Mounting with screw	Cable section (Min-Max)	1-4 mm ²
Material	Plastic	Contains Batteries and/or Accumulator	No
Material quality	Thermoplastic	Connected object	No
Halogen free	Yes		

Documentation

TECHNICAL DOCUMENTATION

 F03232EN-00.pdf | PDF (0.51Mo)

Agreements & Certificates

 LGRP-01347-V01.01-EN.pdf | PDF (0.57Mo)

CATALOGUE PAGE & OTHERS

 ex223001_0699.pdf | PDF (0.1Mo)