



PRODUCT DATASHEET

6" 15/20W DF

LED VALUE DOWNLIGHT ALU GEN2 | Downlights



Product benefits

- Selectable color temperature: 3000K or 4000K or 6500K
- Two versions for structure selection: diffuser version, reflector version
- Luminous flux output of up to 4200 lm
- IP54 rating for the front side of reflector version, indicating water resistance
- Flicker-free driver, ensuring a stable and comfortable lighting experience
- Safety compliance certificates: CB, EU RoHS 2.0, indicating adherence to safety and environmental regulations

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Protection class	II

Photometrical data

Color rendering index Ra	≥80
Beam angle	80 °

Dimensions & Weight

Diameter	174.00 mm
Height	87.00 mm
Product weight	250.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP20/IP54
Dimmable	No
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	LED VALUE DOWNLIGHT ALU GEN2

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854308376	Folding box 1	190 mm x 190 mm x 107 mm	300.00 g	3.86 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854308383	Shipping box 12	400 mm x 400 mm x 340 mm	4099.00 g	54.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.