

**PHILIPS**

**Lighting**



# **HF-Performer Intelligent for TL5 HE/HO lamps**

## **HF-Pi 2 28/35/49/80 TL5 EII**

HF-Performer Intelligent for Master and ECO TL5 HE/HO, TL-D and PL-L lamps. HF-Performer Intelligent features automatic recognition of the connected lamp and is independently able to adjust its operation parameters exactly to the respective lamp. This results in a substantial benefit, especially for T5 lamps, as it means TL5 HE and HO lamps of the same length can be interchanged. With a choice of seven ballasts, the customer is able to handle efficiently every possible combination of Master TL5 and Eco, TL-D, and PL-L lamps. The ballast is primarily designed for Indoor application. For outdoor application, the luminaire should be minimum Classland need to be sufficiently protected against water & dust. The installation should also be guard against any lightening surge or any other necessary electrical protection as deemed in such typical installation & application.

### **Product data**

<b>Operating and Electrical</b>		<b>Wiring</b>	
Input Voltage	220 to 240 V	Connector Type Input Terminals	Insert
Line Frequency	50 to 60 Hz	Connector Type Output Terminals	Insert
Input Frequency	50 to 60 Hz		
Earth Leakage Current (Max)	0.5 mA		
Inrush Current Width	0.37 ms		
Inrush Current Peak (Max)	31 A		
Number of Products on MCB (16A Type B) (Nom)	8		
<b>Temperature</b>			
T-Case Lifetime (Nom)		75 °C	
T-Case Maximum (Max)		75 °C	
<b>Mechanical and Housing</b>			
Housing		L 425x30x22	
Ingress protection code		IP20 [Finger-protected]	

# HF-Performer Intelligent for TL5 HE/HO lamps

Net Weight (Piece)	0.380 kg
--------------------	----------

## Approval and Application

Energy Efficiency Index	A2 BAT
-------------------------	--------

Safety Standard	IEC 61347-2-3
-----------------	---------------

Environmental Standard	ISO 14001
------------------------	-----------

Approval Marks	CE marking ENEC certificate VDE-EMV certificate
----------------	--

CE mark	Yes
---------	-----


Ambient temperature range	-25 °C to 50 °C
---------------------------	-----------------

## Product Data

Order product name	HF-Pi 2 28/35/49/80 TL5 EII
--------------------	-----------------------------

Full product name	HF-Pi 2 28/35/49/80 TL5 EII
Full product code	872790086250800
Order code	913700652666
Material Nr. (12NC)	913700652666
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500881199
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900862508

## Dimensional drawing



Product	D1	C1	A1	A2	B1
HF-Pi 2 28/35/49/80 TL5 EII	4.2 mm	22 mm	425 mm	415 mm	30 mm

